

METHOD AND APPARATUS FOR MOBILE PERSONAL RADAR

FIELD OF THE INVENTION

The present invention relates generally to client/server multimedia applications and more specifically to generation and distribution of personalized multimedia geo-temporal information.

BACKGROUND OF THE INVENTION

In recent years, geo-temporal information has become increasingly important to people and organizations. Geo-temporal information includes natural-phenomenological information pertaining to a particular time period. Geo-temporal information includes also geographic information, such as road and/or traffic conditions, pertaining to a particular time period.

Natural-phenomenological data is collected almost instantaneously from numerous sources. For example, meteorological data is collected from a multitude of individual sites scattered across the world, such as airports, and hydrological data is collected from nearly all of the rivers in the United States. The U.S. National Weather Service maintains a network of approximately 150 Next Generation Weather Radar (NEXRAD) sites across the U.S. Consumer awareness in natural-phenomenological information has also increased as a result of increased participation in outdoor activities and increasingly damaging natural phenomena, such as hurricanes, tornadoes, floods and volcanic activity.

Furthermore, systems for electronic distribution of natural-phenomenological information are commonly available today. Such conventional systems typically include a computer software program running on a client computer that displays periodically reported natural-phenomenological information provided by the National Weather Service that is received through a direct telephone line dial-up connection or an Internet connection. The natural-phenomenological information conventionally includes past, present and forecast meteorological conditions for a number of specific geographic locations including meteorological measures of temperature, relative humidity, wind direction and speed, barometric pressure, wind chill, dew point, precipitation activity,

cloud coverage, satellite images, radar images, aviation-related information, warnings and watches of dangerous natural phenomena such as floods, tornadoes, hurricanes, hail size, speed and direction of the movement of storm cells, wind gusts within storm cells, supercell type, avalanches, brush fires, and forecasts for the local geographic area and the geographic region. Natural-phenomenological information also includes tide cycles, hydrological measures of lakes and rivers, seismological reports and forecasts, ski area snow condition reports, and cosmological events such as sunrise, sunset, and moon phases.

Graphic images of current and/or forecast meteorological conditions are available. For example, the Weather Channel offers graphic images of current or forecast conditions for particular locations. The user enters a zip code or city name into a field in a browser window. A request for a graphic image of the current or forecast meteorological conditions of the zip code or city is sent to the server, and the server returns a graphic image of the meteorological conditions in the vicinity of the zip code or city. The graphic image has labels of large cities and interstate highways. However, the graphic image lacks personalization, such as labels of locations that have any special or personal significance to the user. Furthermore, the image is not centered on the zip code or city. Instead, the same image is used for all zip codes or cities within the boundaries of the image. The server generates a graphic image for a number of portions of the United States, in anticipation of requests. The server will later send the same graphic image for all requests pertaining to the zip code and cities within the boundaries of the image, upon arrival of a request.

The Internet service "MapQuest" enables a user to receive a map of an area that is centered on a location specified by the user. MapQuest also enables the user to zoom the image in and out on the location of interest. However, MapQuest does not include geo-temporal information, or labels of locations that have any special or personal significance to the user other than the location that the image is centered on. In addition, MapQuest does not provide an image of geo-temporal conditions.

For the reasons stated above, and for other reasons stated below which will become apparent to those skilled in the art upon reading and understanding the present specification, there is a need in the art for a system that generates a graphic image of geo-

temporal information that is personalized to the needs of the receiver of the image. Examples of personalization include centering the image on a location of interest, zooming in and out on the location of interest, and labeling locations of interest to the requesting user in the image.

SUMMARY OF THE INVENTION

The above-mentioned shortcomings, disadvantages and problems are addressed by the present invention, which will be understood by reading and studying the following specification.

The present invention enables delivery of personalized radar images to users. Personalization is embodied in the form of images centered over the user's home, or another location of interest, and includes other locations of interest to the user, drawn on the image, and enabling the image to be zoomed in and out in differing ranges.

A client forms a request for a image of geo-temporal information that is centered on a specified location of interest. Alternatively, the request also specifies other personal locations to be labeled in the image. The client sends the request to a first server. The server identifies portions of a base map image, a graphic image of geo-temporal information, and an overlay image that are centered on the location of interest, and that are within a range from the location of interest. The identified portions are combined into a combined image, and which the graphic data of the overlay image is more prominent than the graphic data of the geo-temporal image, and the data of the geo-temporal image is more prominent than the graphic data of the base map image. Later, combined image is modified to indicate the personal locations within the range of the combined image. Thereafter, the image is transmitted from the first server to the client.

The location of interest and personal locations may be identified in a location profile that is stored on second server, or specified in the request. One example of a location specified is the request is a current physical location of the client that is determined from the global positioning system (GPS), or an Internet service provider (ISP) of the client.

In one implementation, the images are formatted as raw graphic data that is not suitable for display by a conventional client computer. In this one implementation, the

present invention also encodes the combined image into a graphic display format before transmitting the combined image.

In one example, the base map image includes well-known topographic landmarks, such as bodies of water. In varying examples, the geo-temporal information includes current and/or forecast geo-temporal information. In one example, the overlay image includes indications of major roadways.

The present invention describes systems, clients, servers, methods, and computer-readable media of varying scope. In addition to the aspects and advantages of the present invention described in this summary, further aspects and advantages of the invention will become apparent by reference to the drawings and by reading the detailed description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of the hardware and operating environment in which different embodiments of the invention can be practiced.

FIG. 2 is a diagram illustrating a system-level overview of an embodiment of the invention.

FIG. 3 is a flowchart of a method for a managing a personalized phenomenological display performed by a client according to an embodiment of the invention.

FIG. 4 is a flowchart of a method for obtaining a location of interest, performed by a client according to an embodiment of the invention.

FIG. 5 is a flowchart of a method for obtaining a location of interest, performed by a server according to an embodiment of the invention.

FIG. 6 is a flowchart of a method for managing personalized phenomenological graphic information performed by a server according to an embodiment of the invention.

FIG. 7 is a flowchart of a method for managing personalized phenomenological graphic information performed by a server according to an embodiment of the invention.

FIG. 8 is an illustration of images involved in managing a personalized phenomenological display on a computer-readable medium according to an embodiment of the invention.

FIG. 9 is an illustration of images involved in managing a personalized phenomenological display on a computer-readable medium according to an embodiment of the invention.

FIG. 10 is a block diagram of server apparatus classes for managing personalized geo-temporal graphic information performed, according to an embodiment of the invention.

FIG. 11 is a block diagram of a server apparatus class for managing locations, according to an embodiment of the invention.

FIG. 12 is a block diagram of a server apparatus class for managing a multiple index color model, according to an embodiment of the invention.

FIG. 13 is a block diagram of a server apparatus class for managing a color model structure, according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of embodiments of the invention, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that logical, mechanical, electrical and other changes may be made without departing from the scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

The detailed description is divided into five sections. In the first section, the hardware and the operating environment in conjunction with which embodiments of the invention may be practiced are described. In the second section, a system level overview of the invention is presented. In the third section, methods for an embodiment of the invention are provided. In the fourth section, a particular object-oriented Internet-based implementation of the invention is described. Finally, in the fifth section, a conclusion of the detailed description is provided.

Hardware and Operating Environment

FIG. 1 is a block diagram of the hardware and operating environment 100 in which different embodiments of the invention can be practiced. The description of FIG. 1 provides an overview of computer hardware and a suitable computing environment in conjunction with which some embodiments of the present invention can be implemented. Embodiments of the present invention are described in terms of a computer executing computer-executable instructions. However, some embodiments of the present invention can be implemented entirely in computer hardware in which the computer-executable instructions are implemented in read-only memory. One embodiment of the invention can also be implemented in client/server computing environments where remote devices that are linked through a communications network perform tasks. Program modules can be located in both local and remote memory storage devices in a distributed computing environment.

Computer 110 is operatively coupled to display device 112, pointing device 115, and keyboard 116. Computer 110 includes a processor 118, commercially available from Intel®, Motorola®, Cyrix® and others, random-access memory (RAM) 120, read-only memory (ROM) 122, and one or more mass storage devices 124, and a system bus 126, that operatively couples various system components including the system memory to the processing unit 118. Mass storage devices 124 are more specifically types of nonvolatile storage media and can include a hard disk drive, a floppy disk drive, an optical disk drive, and a tape cartridge drive. The memory 120, 122, and mass storage devices, 124, are types of computer-readable media. A user enters commands and information into the computer 110 through input devices such as a pointing device 115 and a keyboard 116. Other input devices (not shown) can include a microphone, joystick, game pad, satellite dish, scanner, or the like. The processor 118 executes computer programs stored on the computer-readable media. Embodiments of the present invention are not limited to any type of computer 110. In varying embodiments, computer 110 comprises a PC-compatible computer, a MacOS®-compatible computer or a UNIX-compatible computer. The construction and operation of such computers are well known within the art.

Furthermore, computer 110 can be communicatively connected to the Internet 130 via a communication device 128. Internet 130 connectivity is well known within the art. In one embodiment, a communication device 128 is a modem that responds to communication drivers to connect to the Internet via what is known in the art as a "dial-up connection." In another embodiment, a communication device 128 is an Ethernet or similar hardware (network) card connected to a local-area network (LAN) that itself is connected to the Internet via what is known in the art as a "direct connection" (e.g., T1 line, etc.).

Computer 110 can be operated using at least one operating environment to provide a graphic user interface including a user-controllable pointer. Such operating environments include operating systems such as versions of the Microsoft Windows® and Apple MacOS® operating systems well-known in the art. Embodiments of the present invention are not limited to any particular operating environment, however, and the construction and use of such operating environments are well known within the art. Computer 110 can have at least one web browser application program executing within at least one operating environment, to permit users of computer 110 to access intranet or Internet world-wide-web pages as addressed by Universal Resource Locator (URL) addresses. Such browser application programs include Netscape Navigator® and Microsoft Internet Explorer®.

Display device 112 permits the display of information, including computer, video and other information, for viewing by a user of the computer. Embodiments of the present invention are not limited to any particular display device 112. Such display devices include cathode ray tube (CRT) displays (monitors), as well as flat panel displays such as liquid crystal displays (LCD's). Display device 112 is connected to the system bus 126. In addition to a monitor, computers typically include other peripheral input/output devices such as printers (not shown), speakers, pointing devices and a keyboard. Speakers 113 and 114 enable the audio output of signals. Speakers 113 and 114 are also connected to the system bus 126. Pointing device 115 permits the control of the screen pointer provided by the graphic user interface (GUI) of operating systems such as versions of Microsoft Windows®. Embodiments of the present invention are not limited to any particular pointing device 115. Such pointing devices include mouses,

touch pads, trackballs, remote controls and point sticks. Finally, keyboard 116 permits entry of textual information into computer 110, as known within the art, and embodiments of the present invention are not limited to any particular type of keyboard.

The computer 110 can operate in a networked environment using logical connections to one or more remote computers, such as remote computer 150. These logical connections are achieved by a communication device coupled to, or a part of, the computer 110. Embodiments of the present invention are not limited to a particular type of communications device. The remote computer 150 can be another computer, a server, a router, a network PC, a client, a peer device or other common network node. The logical connections depicted in FIG. 1 include a local-area network (LAN) 151 and a wide-area network (WAN) 152. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN-networking environment, the computer 110 and remote computer 150 are connected to the local network 151 through a network interface or adapter 153, which is one type of communications device. When used in a conventional WAN-networking environment, the computer 110 and remote computer 150 communicate with a WAN 152 through modems (not shown). The modem, which can be internal or external, is connected to the system bus 126. In a networked environment, program modules depicted relative to the computer 110, or portions thereof, can be stored in the remote memory storage device.

System Level Overview

FIG. 2 is a block diagram that provides a system level overview of the operation of embodiments of the present invention. Embodiments of the invention are described as operating in a multi-processing, multi-threaded operating environment on a computer, such as computer 110 in FIG. 1.

System 200 includes a client computer 210 that includes software means 220 for obtaining an image 230 of geo-temporal information. The image 230 is centered on a location of interest 240. The client software means 220 is instrumental in obtaining the image 230 from the server 250. The image 230 is obtained through a command or request 280 to the server 250. Software means 260 on the server 250 generates an image 230 of geo-temporal information that is centered on the location of interest 240.

In another example, the image 230 includes one or more personal locations 270. Personal locations 270 are locations that have been identified as having special importance to the user of the system 200. In varying examples, the personal locations 270 are stored on the client 210 and/or the server 250, or a second server (not shown).

The geo-temporal information is forecast and/or current information pertaining to natural phenomena and/or travel route conditions.

The image 230 is centered on a location of interest 240. Centering the image 230 on a location of interest is useful to the user because locating the location of interest 240 in the image 230 is quicker, and therefore assessing the geo-temporal information relative to the position of the location of interest 240 in the image is faster. A centered location of interest 240 also reduces opportunity for error in visually identifying the location of interest in the image. In contrast to conventional systems, the present invention is useful because the user is enabled to identify those locations, 240 and 270, relative to each other and to the geo-temporal information in the image 230. Also having personal locations 230 integrated into the image 230 enables the user to quickly see and review the geo-temporal conditions of the locations, 240 and 270.

The server software means 260 initializes and loads base map data into memory (not shown) of the server 250. The server software means 260 periodically loads updated radar imagery into the memory, and responds to user hyper-text transfer protocol (HTTP) requests for localized and personalized portions of the imagery data.

The client software means 220 and the server software means 260 are operative on the client 210 and the server 250, respectively. System 200 also includes software means (not shown) for displaying the image 230 of geo-temporal information, operably coupled to the software means 220.

The system level overview of the operation of an embodiment of the invention has been described in this section of the detailed description. A system for requesting and generating images of personalized geo-temporal information. While the invention is not limited to any particular location of interest, software means, image, client and/or server, for sake of clarity, a simplified location of interest, software means, image, client and/or server has been described.

Methods of an Embodiment of the Invention

In the previous section, a system level overview of the operation of an embodiment of the invention was described. In this section, the particular methods performed by the server and the clients of such an embodiment are described by reference to a series of flowcharts. Describing the methods by reference to a flowchart enables one skilled in the art to develop such programs, firmware, or hardware, including such instructions to carry out the methods on suitable computerized clients (the processor of the clients executing the instructions from computer-readable media). Similarly, the methods performed by the server computer programs, firmware, or hardware are also implemented as computer-executable instructions. Methods 300-700 are performed by a client program executing on, or performed by firmware or hardware that is a part of, a computer, such as computer 110 in FIG. 1.

FIG. 3 is a flowchart of a method 300 for a managing a personalized phenomenological display performed by a client according to an embodiment of the invention.

Method 300 fulfills the need in the art for a client obtaining a graphic image of geo-temporal information that is personalized to the needs of the user of the image.

Method 300 includes obtaining a location profile 310. The location profile contains a location of interest, and optionally, one or more personal locations. Obtaining a location of interest is discussed in detail in methods 400 and 500.

Thereafter, a request is generated 320 for a graphic image of geo-temporal information centered on the location of interest. The location of interest may be defined in reference to longitude and latitude or the location of interest may be defined in

reference to the name of the geopolitical position, such as a city. Alternatively, the location of interest may be a current physical location of an electronic device.

The request may include one or more indications of predetermined personal locations. The personal locations may be explicitly identified in the request. Alternatively, the personal locations may be stored on a server, and the personal locations are referenced by the request, such as by using an address of the storage location of the personal locations, or some other unique identification of the personal locations. In another example the personal locations are associated through identification of the user.

In one example, of the request, the request is implemented as an HTTP GET request.

The request may be for an image encoded in Joint Photographic Experts Group (JPEG) format, GIG format, or Portable Network Graphics (PNG) format. The request may be for a static image or a looping image. In the instance of looping images, the request may be for an animated graphics interchange format (GIF) format image. Furthermore, the request may be for an image encoded in a JAVA applet, a browser plug-in such, as Flash® or Shockwave®, or some other browser-based application.

Subsequently, the request is transmitted 330 to a server through a network, such as the Internet.

Thereafter, the geo-temporal information is received, and displayed on a display component associated with the electronic device. Where the client is a personal computer, such as computer 110 in FIG. 1, the geo-temporal information may be displayed on a display device 112 in FIG. 1, and through a web browser application program, such as Netscape Navigator® or Microsoft Internet Explorer®.

Method 300 fulfills the need in the conventional systems for obtaining a graphic image of geo-temporal information that is personalized to the needs of the user of the image as centered on a location of interest of the user, and/or labeled with locations of interest of the user.

FIG. 4 is a flowchart of a method 400 for obtaining a location of interest, as in 310 in FIG. 3, performed by a client according to an embodiment of the invention. In method 400, the location of interest is the current physical location of the electronic device that performs method 400.

Method 400 is one alternative in obtaining a location of interest 310 in FIG. 3.

Method 400 includes transmitting 410 a request for an indication of the current physical location of the electronic device to the server. Thereafter, the indication of the current physical location of the electronic device is received 420 from the server.

In method 400, the electronic device is associated with and/or operated by a user, in which the user is interested in geo-temporal information related to the physical location of the user.

The electronic device can be a mobile electronic device, or a handheld electronic device, such as a cell phone or a wireless personal communication system (PCS) phone.

In yet another example, the handheld electronic device includes a wireless digital assistant device that is operably coupled to the Internet, such as a Palm manufactured by Palm Inc., an Audrey manufactured by 3com, and/or a Pocket PC by Microsoft Corp. In one example of the wireless digital assistant device, obtaining a current physical location of an electronic device includes sending a request for an indication of the proximate or specific, current physical location of the electronic device to a server, and receiving the indication of the location of the electronic device from the server. In one example, the server is a component of an Internet Service Provider (ISP) of the wireless digital assistant device. In another example where the global positioning system (GPS) is used to determine the current physical location of the device, the server is a GPS server.

Where the wireless digital assistant device is a Palm VII, communication with the ISP is implemented using the Palm Query Application (PQA) format. A location-related keyword, such as "zipcode" is transmitted from the Palm to the ISP in PQA format, the keyword is translated by the ISP, and the value of the zip code of the nearest base station to the Palm VII is returned to the Palm VII. The distance between the Palm VII and the nearest base station is typically within five to ten miles of the Palm VII.

The electronic device may also be a fixed-location, non-mobile, electronic device that has a unique identification code. Where the device is operably coupled to the Internet, an example of a unique identification code is an Internet Protocol (IP) address. Furthermore, obtaining a current physical location of an electronic device includes retrieving the Internet Protocol address of the fixed-location electronic device, and obtaining a current physical location of the electronic device from the IP address. In one

example, obtaining a current physical location of the electronic device from the Internet Protocol address includes retrieving the current physical location of the electronic device from a database using the IP address as a key into the database, where the database is implemented on the fixed-location (non-mobile) electronic device, on a local-area network that the device is operably coupled to, or on another device that that fixed-location (non-mobile) electronic device is operably coupled to through a wide-area-network, such as the Internet.

FIG. 5 is a flowchart of a method 500 for obtaining a location of interest in a location profile, as in 310 in FIG. 3, performed by a first server according to an embodiment of the invention. In method 500, the location profile is stored local to a second server.

Method 500 is another alternative in obtaining a location of interest.

Method 500 includes transmitting 510 a request from the first server to the second server, for an address of the location profile. Thereafter, the address of the location profile is received 520 by the first server from the second server. In one example the address is a uniform resource locator (URL).

Thereafter, the first server obtains the location profile 530 using the address that was received in action 520. The location profile is obtained by generating and transmitting a request to the second server for the location profile, and receiving the location profile. In an embodiment where method 500 is implemented on a server that is operably coupled to a client that implements method 300, obtaining a location profile 310 in FIG. 3, is not performed by the client, but is instead performed by the first server in response to receiving the request from the client.

Subsequently, the location profile is obtained using the received address. The received address is used to formulate a request for the location profile. The request is transmitted to the second server, and the location profile is received by the first server.

FIG. 6 is a flowchart of a method 600 for managing personalized phenomenological graphic information performed, by a server according to an embodiment of the invention.

Method 600 fulfills the need in the art of a graphic image of geo-temporal information that is personalized to the needs of the user of the image.

Method 600 includes receiving a base map image 610 of a geographic area, such as a base map of the United States of America. The base map image includes well-known topographic landmarks, such as bodies of water. The base map is depicted as image 810 in FIG. 8 and image 910 in FIG. 9.

Method 600 also includes receiving a graphic image of geo-temporal information that corresponds to the base map image 620. In varying examples, the geo-temporal information is current and/or forecast geo-temporal information.

A request for a graphic image of geo-temporal information is received 630. The request expressly indicates, or is interpreted to indicate, that geo-temporal information centered on a location of interest, within a physical distance range of the location of interest, is requested. In other examples, the request is embodied as a command or instruction. In further examples, the request is for a singular graphic image of geo-temporal information, or the request is for periodic transmissions of at least one graphic image of geo-temporal information.

In varying embodiments, receiving the graphic image 620 of geo-temporal information is performed before, during, and/or after the receiving the base map image 610.

After receiving the images in actions 610 and 620, the graphic image of geo-temporal information is combined with the base map image 640. The combining yields a combined graphic image data structure. In other examples, the combining action is overlaying and/or boolean adding of the images.

In one example, receiving the request 630 is performed before the combining 640. In other examples, receiving the request 630 is performed during and/or after the combining 640. However, in all situations, the request is received 630 before the method progresses past the combining 640.

After combining the images, method 600 includes identifying a portion of the combined graphic image that corresponds to the location of interest and the physical distance range 650. The request that is received in action 630 is the source of the location of interest. The source of the distance range, in varying examples, is the request, or a data source operably coupled to the server. In the example of the data source operably coupled to the server, the distance range may be a uniform distance range that is used for

all requests, or the distance range may be associated with the user. The user may also more generally be a unique identification of the source of the request.

In one example, where the base map image and the graphic image are in the form of raw image data, not formatted for display, the portion is encoded with a graphics file format 670, and the encoded data structure is transmitted 680.

In one example of transmitting 680, the encoded data structure is transmitted to the source/sender of the request. In other examples where the encoded data structure is periodically transmitted, the periodic transmission is performed at a predetermined time period and/or when certain geo-temporal information exceeds one or more predetermined trigger/threshold values.

In one variation of method 600, the request includes indications of predetermined personal locations, within the physical distance range of the location of interest, and method 600 includes modifying the portion with labels that indicate the personal locations. In varying embodiments, the indications of predetermined personal locations include names, longitude and latitude locations, and/or keys into lists or tables of personal locations that are stored local to the server.

In another variation, method 600 includes encoding the data structure with a graphics file format. The encoding is performed after the overlying 640. In one example, an indication of the graphics file format is included in the request. In another example, the server that performs method 600 is dedicated to serving a specific type of device, or class of devices, that originated the request. The device or class of devices share at least one characteristic in common: the requirement and/or ability to support a particular graphics file format. The particular graphics file format is predetermined before the operation of method 600, and the particular graphics file format used in the encoding.

In yet another variation, the identifying action 650 includes identifying a portion of the combined graphic image, the portion having a center corresponding to the location of interest, and the portion having an outer boundary corresponding to the physical distance range from the center.

In still another embodiment, the actions of receiving a geo-temporal image 620, overlying 640, identifying 650, copying 660, encoding 670 and transmitting 680 are

performed repeatedly in response to a request received in action 630 for periodic updates and/or update when specific geo-temporal information exceeds a threshold value.

Method 600 fulfills the need of the conventional systems for obtaining a graphic image of geo-temporal information that is personalized to the needs of the user of the image as centered on a location of interest of the user, and labeled with locations of interest of the user.

FIG. 7 is a flowchart of a method 700 for managing personalized phenomenological graphic information performed, by a server according to an embodiment of the invention.

Method 700 fulfills the need in the art of a graphic image of geo-temporal information that is personalized to the needs of the user of the image.

Method 700 includes receiving a base map image 710 of a geographic area, such as a base map of the United States of America. The base map image includes well-known topographic landmarks, such as bodies of water. The base map is depicted as image 810 in FIG. 8 and image 910 in FIG. 9.

Method 700 also includes receiving a graphic image of geo-temporal information that corresponds to the base map image 720. In varying examples, the geo-temporal information is current and/or forecast geo-temporal information. The graphic image of geo-temporal information is depicted as image 820 in FIG. 8 and image 920 in FIG. 9.

A request for a graphic image of geo-temporal information is received 730. The request expressly indicates, or is interpreted to indicate, that geo-temporal information centered on a location of interest, within a physical distance range of the location of interest, is requested. In other examples, the request is embodied as a command or instruction. In further examples, the request is for a singular graphic image of geo-temporal information, or the request is for periodic transmissions of at least one graphic image of geo-temporal information.

In varying embodiments, receiving the graphic image 720 of geo-temporal information is performed before, during, and/or after receiving 710 the base map image.

After receiving the images in actions 710 and 720, the graphic image of geo-temporal information is combined with the base map image 740. The combining yields a first combined graphic image data structure. The geo-temporal information is integrated

prominently in the hierarchy of the overlay because the geo-temporal information is prominent in the interest of the user. In other examples, the combining action is combining and/or boolean adding of the images. The graphic image of geo-temporal information is depicted as image 820 in FIG. 8 and image 920 in FIG. 9. The geo-temporal information is integrated prominently in the hierarchy of the overlay because the geo-temporal information is prominent in the interest of the user.

After generating the first combined image, a second combined image is created 745 from the first combined image and an image of geo-political information. Geo-political information includes state and international boundaries, and roads. The image of geo-political information is depicted as image 840 in FIG. 8 and image 940 in FIG. 9. The second combined graphic image is depicted as image 850 in FIG. 8 and image 950 in FIG. 9. . The geo-political information is integrated more prominently in the hierarchy of the overlays because the geo-political information is typically necessary in order for the user to visually determine the position of the geo-temporal information

In one example, receiving the request 730 is performed before the combining action 740 or the combining action 745. In other examples, receiving the request 730 is performed during and/or after the combining 740 or combining 745. However, in all situations, the request is received 730 before the method progresses past the combining 745.

After combining the images, method 700 includes identifying a portion 750 of the second combined graphic image that is centered on the location of interest, and having a physical distance range. The source of the location of interest is the request that was received in action 730. The source of the distance range of the portion, in varying examples, is the request received in action 730, or a data source operably coupled to the server. In the example of the data source operably coupled to the server, the distance range may be a uniform distance range that is used for all requests, or the distance range may be associated with the user. The user may also more generally be a unique identification of the source of the request.

Subsequently, the identified portion is copied to a data structure 760 in preparation for final processing.

Thereafter, the data structure is modified with personalization information 765, such as the location of interest, personal locations and/or a localized date/time stamp. The personalization information is depicted as data 860 in FIG. 8 and data 860 in FIG. 9.

Subsequently, in one example, where the base map image and the graphic image are in the form of raw image data, not formatted for display, the portion is encoded with a graphics file format 770, and the encoded data structure is transmitted 780.

In one example of transmitting 780, the encoded data structure is transmitted to the source/sender of the request. In other examples where the encoded data structure is periodically transmitted, the periodic transmission is performed at a predetermined time period and/or when certain geo-temporal information exceeds one or more predetermined trigger/threshold values.

In one variation of method 700, the request includes indications of predetermined personal locations, within the physical distance range of the location of interest, and method 700 includes modifying the portion with labels that indicate the personal locations. In varying embodiments, the indications of predetermined personal locations include names, longitude and latitude locations, and/or keys into lists or tables of personal locations that are stored local to the server.

In another variation, method 700 includes encoding the data structure with a graphics file format. The encoding is performed after the overlying 740. In one example, an indication of the graphics file format is included in the request. In another example, the server that performs method 700 is dedicated to serving a specific type of device, or class of devices, that originated the request. The device, or class of devices, share at least one characteristic in common: The requirement and/or ability to support a particular graphics file format. The particular graphics file format is predetermined before the operation of method 700, and the particular graphics file format used in the encoding.

In yet another variation, the identifying action 750 includes identifying a portion of the combined graphic image, the portion having a center corresponding to the location of interest, and the portion having an outer boundary corresponding to the physical distance range from the center.

Method 700 fulfills the need of the conventional systems for obtaining a graphic image of geo-temporal information that is personalized to the needs of the user of the

image as centered on a location of interest of the user, and labeled with locations of interest of the user.

According to yet another embodiment of a method of the invention, the location of a mobile device, and in particular a WAP-enabled mobile phone, is determined by what cell of a cell phone system the mobile phone is currently being serviced by. In one such example embodiment, the cell phone system produces location data that is supplied to the user's cell phone. This location data for example is the zip code of the area that the user is most likely in or proximate to while using the mobile phone, as determined by the phone system cell providing service to the mobile phone. As the user passes from one cell to the next while traveling, the zip code location is in turn updated to the mobile phone. In this example embodiment, the zip code is in turn used by the mobile phone to automatically inform the personal weather server of the location of the mobile phone. In this manner, the personal weather feed to the mobile device may be continuously updated automatically as the user's location changes.

According to yet other example embodiments, the same approach is used in the case of a personal digital assistant adapted for wireless Internet access. In such systems using cell technology, the same type of approach is applied, allowing the location of the personal digital assistant to be automatically fed to the assistant by determination of the cell that the digital assistant is being serviced by for wireless Internet service. In still other example embodiments, the cell telephone system or wireless Internet service provider provides the user's location directly to the personal weather server, as opposed to routing such information through the mobile phone or digital assistant.

In yet other example embodiments, the location of the mobile device using a cell phone system infrastructure is determined by the process of triangulation, in which the signal strength or other characteristic of the mobile device transmissions are measured at the receivers of several different cell site installations and the relative comparison of the signals allows the location of the device to be more accurately determined.

In still another example embodiment, the mobile device includes a global positioning system that can determine the location of the mobile device by reference to GPS satellites. The location is determined at the mobile device, and in turn reported to

the personal weather server. This approach allows a highly accurate determination of the mobile device's location using widely available technology.

In yet another example embodiment, the mobile device is itself a GPS unit that is wireless enabled allowing for wireless communication to the personal weather server either through a private network or the Internet. This device includes a display, typically an LCD, for displaying the user's location and other location-related data to the user. In one embodiment, the display is a text-based display for displaying location coordinates and other statistics. In another embodiment, it is a graphical display that can display a map showing the user's location or another area of interest to the user.

In this example embodiment, the wireless GPS unit can be used to request personal weather maps for any area of interest to the user, but in particular the unit can display a continuously updated weather map that is centered on the user's current location or otherwise oriented to show the weather conditions from the unique geographical location of the user. The continuously or periodically updated map would be recentered or reoriented taking into account changes in the user's location as determined by the GPS circuits. Further, in one example embodiment, the speed and direction of the user is determined and used to determine the estimated time of arrival of the user to a storm system or other meteorological condition or event of interest. For example, the wireless GPS unit may report to the user that they are going to arrive upon a thunderstorm within a certain period of time, and thus allow the user to take precautionary steps or avoid the storm altogether. Of course, this same functionality may be provided using other mobile devices such as a WAP-enabled phone as described above provided that the device's location can be automatically determined in a sufficient manner.

In yet other example embodiments, the above-described functions may be obtained by the user manually entering their location information into the mobile device, such as a mile marker on a freeway, and providing the user's rate of speed and direction. Using this information, any weather conditions or events the user may be approaching can also be brought to the user's attention.

In other embodiments of the methods, the methods are implemented as a computer data signal embodied in a carrier wave, that represents a sequence of

instructions which, when executed by a processor, such as processor 118 in FIG. 1, that cause the processor to perform the respective implemented methods.

Implementation

Referring to FIGS. 8-13, implementations of the invention are described in conjunction with the system overview in FIG. 2 and the methods described in conjunction with FIGS. 300-700.

FIG. 8 is an illustration of images 800 involved in managing a personalized phenomenological display on a computer-readable medium according to an embodiment of the invention.

The present invention combines graphic data that represents a base map image of well-known landmarks 810 with overlying graphic data that represents geo-temporal information 820 and with overlying image 840, yielding a combined image 850. Subsequently, the combined image 850 is modified with personalization information 860, such as an indication of the location of interest 885. A portion of the combined graphic data, having as its center a location of personal interest 860 to the user, is copied from the combined graphic data. In the illustrated example 800, the location of personal interest 885 to the user is "My House." The result is a data structure 880 that is personalized to the geo-temporal information needs of the user.

In another embodiment, the data structure 880 is modified with graphic data representing at least one personal location 870. In the illustrated example 800, the personal location 870 is "Campus." The result is a data structure 880 that is similarly personalized to the geo-temporal information needs of the user.

In yet another embodiment, the data structure 880 is modified with graphic data representing a date/time stamp 890. In the illustrated example 800, the date/time stamp 890 is located in the bottom right-hand corner of the image 880.

In yet another embodiment, data structure 880 is the product of the process of method 700.

FIG. 9 is an illustration of images 900 involved in managing a personalized phenomenological display on a computer-readable medium according to an embodiment

of the invention. FIG. 9 illustrates the images involved in a process that is substantially similar to the illustration of FIG. 8, but using a wider range, or field of view, than FIG. 8.

The present invention combines graphic data that represents a base map image of well-known landmarks 910 with overlying graphic data that represents geo-temporal information 920 and with overlying image 940, yielding a combined image 950. The combining of images 910 and 920 is described in combining 740 in FIG. 7. Overlay image 940 includes graphic geo-political and/or road information. The combining of images 910, 920 and 940 is described in combining 745 in FIG. 7. Subsequently, the combined image 950 is modified with personalization information 960, such as indications of the location of interest. The modification of image 950 with personalization information 960 is described in the modifying action 765 in FIG. 7. A portion of the combined graphic data, having as it's center a location of personal interest 960 to the user, is copied from the combined graphic data. In the illustrated example 900, the location of personal interest 960 to the user is "My House." The result is a data structure 980 that is personalized to the geo-temporal information needs of the user.

In another embodiment, the data structure 980 is modified with graphic data representing at least one personal location 970. In the illustrated example 900, the personal locations 970 are "Campus," "Soldier Field" and "Lambeau Field." The result is a data structure 980 that is similarly personalized to the geo-temporal information needs of the user as data structure 880. The modification of image 950 with personalization information 960 is described in the modifying action 765 in FIG. 7.

In yet another embodiment, the data structure 980 is modified with graphic data representing a date/time stamp 990. In the illustrated example 900, the date/time stamp 990 is located in the bottom right-hand corner of the image 980.

In yet another embodiment, data structure 980 is the product of the process of method 700.

FIG. 10 is a block diagram of server apparatus classes 1000 for managing personalized geo-temporal graphic information performed, according to an embodiment of the invention.

The block diagram of server apparatus classes 1000 depicts the class relationships in a single instance of the server apparatus objects 1000. The server apparatus classes 1000 are implemented as a Java program, operating in a single Java virtual machine.

The server apparatus classes 1000 have the following basic functions: Initialization and loading of base map data, as in image 810 in FIG. 8 and image 910 in FIG. 9, into program memory, followed by periodic loading of new radar imagery into memory, and responding to user hyper-text transfer protocol (HTTP) requests for localized and personalized portions of the imagery data.

In the class diagram 1000, each box generally corresponds to one or more instances, or objects, of the named class. The box contents consist of the class name, e.g. "ImageServlet", followed by a line and then a list of member variables that are prefixed by a dash. The member variables are the data of the object. Below a double line is a list of class methods. The methods are functions of the object. Class diagram 1000 shows public class methods, i.e. each class's public interface. The lines between the objects in diagram 1000 define the relationship between the objects. Class diagram 1000 uses the Unified Modeling Language (UML) notation, which is the industry-standard language for specifying, visualizing, constructing, and documenting the object-oriented artifacts of software systems. In the figures, a hollow arrow between classes is used to indicate that a child class below a parent class inherits attributes and methods from the parent class. In addition, a hollow diamond is used to indicate that an object of the class that is closest to the hollow diamond is composed of the other object connected through a line. Composition defines the attributes of an instance of a class as containing an instance of one or more existing instances of other classes in which the composing object does not inherit from the object(s) it is composed of.

The diagram depicts public interfaces of the server apparatus classes 1000. Managing varying maps sizes allows the system to display various scales of the requested image with aesthetic base map images, as in image 810 in FIG. 8 and image 910 in FIG. 9. Recycling of objects leads to faster server performance. Multiple image types refers to creating images for devices which support other image type, such as Palm devices, which support only four colors.

The ImageServlet class 1010 extends Java's HTTPServlet class 1020. The purpose of the ImageServlet class 1010 is to serve HTTP GET and POST requests. The ImageServlet class 1010 init() class method is invoked by the web server. The web server is external to the apparatus classes depicted. A "configuration" parameter of the init() class method contains the path to a properties file (not shown) of the server apparatus. The properties file contains configuration information in the server. The configuration information is used to initialize objects of the ImageServlet class 1010. . Object of the ImageServlet class 1010 loads the configuration information into a Properties object (not shown), which Properties object uses to create an object (not shown) of the ImageHandler class 1030.

An object (not shown) of the ImageHandler class 1030 manages an object (not shown) of the ImageLoader class 1040. The object of the ImageLoader class 1040 loads periodic new radar images, and an object of the ClipMaker class 1050 constructs clips requested by the user. The object of the ImageHandler class 1030 is instantiated with a Properties object that contains all the necessary information to create these two main objects and initializes the object system. Hence, the object of the ImageHandler class 1030 unpacks the Properties object and instantiates an object of the ImageLoader 1040 and instantiates an object of the ImageHandler class 1030.

During initialization, the object of the ImageHandler class 1030 loads the base map images, such as in action 610 in FIG. 6 and action 710 in FIG. 7. The loading transforms the data from the maps' raw data files and colormap files into BufferedImages. These large BufferedImages, along with the large BufferedImages created by the periodic loading of radar image data, wait in memory to be read by the image clip making process during user requests. The clip making process, bypasses the BufferedImage application program interface of Java and works directly with the data in the byte arrays.

In loading the base map images, as in image 810 in FIG. 8 and image 910 in FIG. 9, the object (not shown) of the ImageHandler class 1030 relies on functionality contained in an object (not shown) of the RawImageTools class 1060. The object of the RawImageTools class 1060 is a collection of static class methods useful for manipulating raw image files and color map configuration files. "Raw" image files are files in which each byte represents a single pixel and references the indexed color of that pixel. The

map of indexes to colors is specified in a separate color map configuration file. The ImageLoader 1040 and ClipMaker 1050 classes also use the functionality of RawImageTools 1060.

Periodic Loading of New Radar Image Data

The image loading process pre-supposes the existence of a process which supplies the imagery data. The data comes from a program which processes purchased data from a third party or from a program which processes the National Weather Services' Next Generation Weather Radar (NEXRAD) feed over access to NOAA real-time database system (NOAAPORT.) This external process places data into the proper location on the file system local to the objects of the server apparatus classes 1000.

The ImageLoader 1040 object is initialized with all information necessary to start and continue loading image data files on a periodic basis. The constructor for this class is the only public interface. During construction, an internal thread is started which loads the initial images and periodically checks the file system for new files. Enough images to form the image loop are loaded the first time through. When the ImageLoader 1040 object finds a new image file during the periodic check, it loads the image.

Image loading consists of the following:

- Finding a file in a specific directory on the file system with a name consisting of the specified prefix, a timestamp for the file's contents, and a suffix of ".raw". The file's timestamp must indicate a time following the last file which was loaded.
- Decompressing the file's contents (it was compressed by the process with created it).
- Reading the raw data from the file and combining it and a pre-configured color map into objects which comprise a BufferedImage object -- IndexColorModel, DataBufferByte, and WriteableRaster.
- Creating and returning the BufferedImage.

The date/time of each image is also extracted. The images and date/times are given to the object of the ImageHandler class 1030 for management. ImageHandler class 1030 does necessary scaling of the imagery to support the various map sizes, and constructs objects (not shown) of the MappedImage 1070 class and objects (not shown) of the MappedLoop class (not shown) for use by the ClipMaker object.

The MappedImage 1070 class consists of the image data for image and transformation information. The transformation information, in the form of an AffineTransform, maps latitude/longitude space to image pixel space. MappedLoop is similar to MappedImage 1070, but manages arrays of images rather than a single image.

Managing of Requests for Image Clips

ImageServlet 1010 doGet() class method is the HTTP GET interface: ImageServlet 1010 receives requests for image clips through this class method's "request" parameter; it sends responses, in known graphics formats such as PNG, JPEG, and GIF, back through the class method's "response" parameter. ImageServlet 1010 extracts the location and other image specifications from the request and hands most of the work of creating the image clip to the ImageHandler class 1030. ImageHandler class 1030 returns the data for the completed clip back in the form of a BufferedImage. ImageHandler class 1030 encodes the image data into the required graphics image format and returns the data to the requestor, as in action 630 in FIG. 6 and action 730 and FIG. 7.

The ImageHandler class 1030 getClip() class method uses the information contained in its parameter to request a clip of ClipMaker 1050. ClipMaker 1050 contains all necessary images, times, transformations, and color maps. The input to the clip making algorithm for each request are the parameters to the requestClip class method: 1) an array of locations, the first in the array specifying the center location; 2) the requested clip size of the image; 3) the scale of the image, where 100 represents the basic, agreed upon size (currently about 2 pixels to a kilometer), scale = 50 is half that size, etc; 4) the timezone to use in making the time stamp on the image; and 5) a boolean indicating whether this will be a loop – an array of images, or not.

The final image will consist of the combining of three images -- the underlying base map image, as in image 810 in FIG. 8 and image 910 in FIG. 9, the imagery, as in image 820 in FIG. 8 and image 910 in FIG. 9, and the overlay base map, as in image 840 in FIG. 8 and image 940 in FIG. 9, plus a timestamp and locations drawn on the image. The locations are represented by a hash mark on the exact location of the image, next to which is drawn the location name.

The underlying base map image is the part of the base map which lies underneath radar imagery, “overlay” parts will appear over the radar imagery. Land and lakes underlie the radar imagery, state lines, county lines, and interstates are overlaid on the radar imagery.

The three images are combined by the following method:

1. Obtain or create a byte array that will be the image data of the final image.
2. Obtain the appropriate three maps that will be the three layers, based on requested scale.
3. Using the requested image width and height, the image scale, and center location and the appropriate transformations, find pointers to first pixel to be used in each of the three layers.
4. For each pixel in the final image final, taking width and height into account:
 - Update pointers to the appropriate pixels of each layers.
 - Check the pixel in the topmost layer. If opaque, make that pixel's color the color of the pixel in the final image. This is done using pre-calculated mappings between the various images' color index tables.
 - If the pixel in the topmost layer is transparent, check the pixel in the second layer. If that is opaque, make that pixel's color the color of the pixel in the final image.
 - If the pixel in the second layer and the topmost layer are transparent, use the color of the pixel in the bottom layer for the color in the final image.

The resulting data structure is made into a BufferedImage by combining it with the appropriate IndexColorModel. Examples of the resulting data structure are image 850 in FIG. 8 and image 950 in FIG. 9. Using the BufferedImage API's drawString() method, the time stamp and the location strings are drawn onto the image. The drawing of the location strings also involves an process for determining the placement of the locations and the strings and ensuring multiple locations do not overlap.

The resulting BufferedImage is returned and, as noted, converted to the appropriate graphics format before being sent back to the requestor.

The apparatus 1000 components can be embodied as computer hardware circuitry or as a computer-readable program, or a combination of both. In another embodiment, apparatus 1000 is implemented in an application service provider (ASP) system.

More specifically, in the computer-readable program embodiment, the programs can be structured in an object-orientation using an object-oriented language such as Java, Smalltalk or C++, and the programs can be structured in a procedural-orientation using a procedural language such as COBOL or C. The software components communicate in any of a number of means that are well-known to those skilled in the art, such as application program interfaces (A.P.I.) or interprocess communication techniques such as remote procedure call (R.P.C.), common object request broker architecture (CORBA), Component Object Model (COM), Distributed Component Object Model (DCOM), Distributed System Object Model (DSOM) and Remote Method Invocation (RMI). The components execute on as few as one computer as in computer 110 in FIG. 1, or on at least as many computers as there are components.

FIG. 11 is a block diagram of a server apparatus class 1100 for managing locations, according to an embodiment of the invention.

Each instance of the location class 1100 represents a single user location and consists of a location name and a latitude and longitude.

FIG. 12 is a block diagram of a server apparatus class 1200 for managing a multiple index color model, according to an embodiment of the invention.

Class MultiIndexColorModel 1200 stores information about the various map and radar images' color models and mappings between color models. The MultiIndexColorModel 1200 class implements IndexColorModel Java class that uses a limited set of discreet colors having reduced memory requirements. Other embodiments implement other ColorModel classes. IndexColorModels of varying bit sizes are implemented. In one embodiment, a ColorModel class with 256 colors requires eight bits (one byte) for each pixel in the image. In another embodiment, a ColorModel class with four colors requires two bits for each pixel is implemented.

FIG. 13 is a block diagram of a server apparatus class 1300 for managing a color model structure, according to an embodiment of the invention.

Class ColorModelStruct 1300 stores information about the various map and radar images' color models and mappings between color models. The ColorModelStruct class 1300 implements ColorModelStruct Java class that uses a limited set of discrete colors having reduced memory requirements. Other embodiments implement other ColorModel classes. IndexColorModels of varying bit sizes are implemented. In one embodiment, a ColorModel class with 256 colors requires eight bits (one byte) for each pixel in the image. In another embodiment, a ColorModel class with four colors requires two bits for each pixel.

Conclusion

A method and apparatus for personal radar has been described.

Systems and methods are provided through which a radar image centered on a location of interest, is displayed. Alternatively, other predetermined personal locations that are within the range of the radar display are also displayed in the radar image. The personal locations are stored in a database, and the location of interest is selected from the personal locations. The radar image is dynamic, and changes when a different location of interest is selected from the list of personal locations. In another embodiment, the location of interest is the current physical location of the computer

Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement which is calculated to achieve the same purpose may be substituted for the specific embodiments shown. This application is intended to cover any adaptations or variations of the present invention. For example, although described in object-oriented terms, one of ordinary skill in the art will appreciate that the invention can be implemented in a procedural design environment or any other design environment that provides the required relationships.

In particular, one of skill in the art will readily appreciate that the names of the methods and apparatus are not intended to limit embodiments of the invention. Furthermore, additional methods and apparatus can be added to the components, functions can be rearranged among the components, and new components to correspond to future enhancements and physical devices used in embodiments of the invention can be introduced without departing from the scope of embodiments of the invention. One of

skill in the art will readily recognize that embodiments of the invention are applicable to future communication devices, different file systems, and new data types.

The terminology used in this application with respect to is meant to include all object-oriented, database and communication environments and alternate technologies which provide the same functionality as described herein. Therefore, it is manifestly intended that this invention be limited only by the following claims and equivalents thereof.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217